

EXHIBIT A -9

Long Sleeve Shirt Specifications and Sizes – Male & Female (unless indicated, specifications are the same for male and female long sleeve uniform shirts.)

PORT OF ENTRY (POE) LONG SLEEVE SHIRT CLASS A

DESCRIPTION: Long Sleeve (L/S) Poly Wool Shirt – Port of Entry Class A

COLOR: NAVY

FABRIC: TIC Poly/ Wool / Sorona 9 1/2 oz. Tropical Weave w/ PURE Finish (Or CSP approved equivalent with a minimum of grade 4 for pilling)

CONSTRUCTION / DETAILS:

STYLE:

The Shirt shall be standard military style with shirttails and permanently stitched two (2) front and three (3) back creases.

TAILORING:

This garment shall be constructed according to the principles set forth in the specifications. All stitches shall be of the proper tension and size so as to avoid puckering after the shirt has been laundered and to give best durable press performance. All sewing shall be with polyester core thread to match shirt fabric. The collar and cuffs are to be single stitched 1/4" from edge. The pockets, flaps and epaulets shall be edge stitched.

COLLAR:

Dress style collar - The collar points shall be medium spread approximately 3" in length. The outside edge of the collar shall be stitched with a 1/4" edge stitch. The collar width at the back of the neck shall be 1 3/4". The back of the stand shall measure 1-1/2". The inside collar shall be made of a sateen fabric for comfort. There shall be a collar stay sewn inside the collar along the bottom edge of each collar to hold the collar shape and still allow the attachment of collar brass. There shall be hidden, button-down tabs sewn underneath each collar point to keep the collar secure. These tabs shall attach to hidden durable ligne 14 buttons to keep the collar secure.

YOKE:

The garment shall have a straight yoke back located approximately 4 1/4" below the collar seam. The inside yoke shall be lined with 100% Polyester Taffeta.

SLEEVES:

The sleeves shall be one piece sewn into the shoulder, tapering into the finished cuffs with pressed double pleats. The cuffs shall be attached to the sleeve with a 3/8" double needle stitch and shall be 2-5/8" in width; fastening with two durable ligne 20 4 hole 100% polyester buttons. The cuffs shall be made of two pieces of base shirt material with an interlining. There shall be a shirt cuff opening with a facing of shirt material 7" X 1" tapering to a point with a closure stitch across the facing 1 1/2" from the point. There shall be a buttonhole approximately 4" from the point to attach a ligne 16 durable 100% polyester button. The button shall be attached to the inside facing which shall be bound with 5/8" bias cut shirt material for reinforcement. The sleeves and side closing seams shall be attached to the body of the shirt with a merrow and a safety stitch for reinforcement.

EPAULETS-Male:

The epaulet shall button at point 1" from the collar seam. The Epaulet shall be 2 1/8" wide at the shoulder seam and taper to 1 5/8", then to a point. The overall length of the epaulet shall be approximately 8". The epaulet shall be double thickness with a single edge stitch on the perimeter. The epaulets shall be box stitched to shoulders with row of cross-stitching 2 1/2" from sleeve head seam. There shall be a hidden ligne 16 button attached 1 3/8" from the epaulet attachment button on each side under each epaulet to attach a unique microphone sling (patent applied for) to ensure that the radio microphone is in the proper place to be deployed.

EPAULETS-Female:

The epaulets shall be sewn onto the shoulder seam and shall extend to within 1/2" of the collar seam. The epaulet shall button at point 1" from the collar seam. The Epaulet shall be 2" wide at the shoulder seam and taper to 1 1/2", then to a point. The overall length of the epaulet shall be approximately 5 5/8". The epaulet shall be double thickness with a single edge stitch on the perimeter. . The epaulets shall be box stitched to shoulders with row of cross-stitching 2 1/2" from sleeve head seam. There shall be a hidden ligne 16 button attached 1 3/8" from the epaulet attachment button on each side under each epaulet to attach a unique microphone sling (patent applied for) to insure that the radio microphone is in the proper place to be deployed.

FRONT:

The front shall have a center facing 1-1/2" wide placket extending from the collar stand to the bottom of shirt. The placket shall have an interlining for stability and a neat appearance and shall be 1/4" top stitched on each side. The center front shall contain six (6) vertical buttonholes placed 3/4" from edge and 3-1/2" apart. There shall be a button at the neck corresponding with the top buttonhole, which shall be set horizontally. There shall be a hidden zipper sewn under the center front placket. There shall be an inside facing of self-material on the button side 3 1/4" wide extending from the collar stand to bottom of shirt. The buttons shall be securely attached shall correspond to the buttonholes on the center facing. There shall be a spare line 20 and line 16 button sewn into the inside button facing. There shall be 4 bands of silicone approximately 3" long by 1/2" wide sewn into the bottom of the shirt 2" from the bottom and 1/4" on the inside of the outer creases designed to work with the waistband in the Class B / POE trousers to act as a shirt retention device.

POCKETS-Male:

The shirt shall have two Military-styled box pleated, breast patch pockets with 3-point button down flaps. The breast pocket shall be 5 5/8" wide X 6 3/8" long. The center pleat shall be 1 1/2" wide. The bottom corners of the pocket shall be cut on a 40 degree angle and shall be 1 1/4" long. The pocket flaps shall be slightly tapered and shall be 6" wide at the top and 6 1/4" wide at the outside points on the bottom of the flap. (Pocket dimensions will vary with size) The flaps shall be attached to the shirt body 1/4" above the top of the pocket, resulting in a complete pocket measurement of 6 3/8" long. The pocket shall be edge stitched around the perimeter and shall finish with a 3/8" turn down. The pocket corners shall be reinforced with a triangle stitch in each corner. There shall be a pencil opening on both the left and right flap. The two outside points of each pocket flap shall have concealed Velcro closures. The left breast pocket shall have a sewn pencil compartment approximately 1-5/8" wide. Each flap shall have a ligne 20 buttons sewn to a false buttonhole on the surface of the flap.

POCKETS-Female:

The shirt shall have two Military-styled box pleated, breast patch pockets with 3-point button down flaps. The breast pocket shall be 5 1/4" wide X 5 3/8" long. The center pleat shall be 1 1/8" wide. The bottom corners of the pocket shall be cut on a 40 degree angle and shall be 1 1/4" long. The pocket flaps shall be slightly tapered and shall be 5 3/8" wide at the top and 5 1/4" wide at the outside points on the bottom of the flap. (Pocket dimensions will vary with size) The flaps shall be attached to the shirt body 1/4" above the top of the pocket, resulting in a complete pocket measurement of 6" long. The pocket shall be edge stitched around the perimeter and shall finish with a 3/8" turn down. The pocket corners shall be reinforced with a triangle stitch in each corner. There shall be a pencil opening on both the left and right flap. The two outside points of each pocket flap shall have concealed Velcro closures. The left breast pocket shall have a sewn pencil compartment approximately 1-5/8" wide. Each flap shall have a ligne 20 buttons sewn to a false buttonhole on the surface of the flap.

HIDDEN CHEST POCKET:

There shall be a #3 YKK 6 1/2" concealed zipper under the front placket on the right side of the male shirt and left side of the female shirt accessing a hidden pocket. The pocket height shall be 9" with the pocket extending from the facing seam to the side seam. The center of the zippered opening shall be centered at the midpoint between the top of the chest flap and the bottom of the chest pocket. The top of the concealed pocket shall align with the top of the pocket flap for internal stability. The pocket shall be made of shirting material.

BADGE TAB:

The badge tab is to be reinforced on inside of the shirt by means of a strip of material 1" wide edge stitched and folded so that no raw edges show. The reinforcement strip is to extend from the flap setting stitch to the joining seam at the front of the yoke. There shall be two small (horizontal) buttonholes, 1-1/4" apart sewn through the left front and the reinforcement strip with the bottom buttonhole located 1-1/4"

CREASING:

Pockets and pocket flaps shall be uniform in shape and size. The front and back creases shall incorporate a permanent 1/16" stitched crease.

Back: The shirt shall have 3 permanent creases, 1/16" wide on the back panel. One crease shall be located at the center back and shall start at the center of the yoke and continue straight down to the bottom edge of the shirt. Each of the other two creases shall be located at the midway point between the center crease and the shoulder seam on both the left and right sides of the center crease.

Front: The shirt shall also have two permanent stitched 1/16" wide military creases down each side from the shoulder seam to the bottom of the shirt centered through each front pocket and pocket flap.

BUTTONS:

All buttons shall be 100% Polyester and shall pass ASTM 5171-1191.84 kg mass dropped from a height of 67mm.

LABELS:

All shirts will be finished with a woven (not printed) label, permanently affixed. It will include the correct fiber content of the fabric and identification of brand as well as garment care instructions.

EMBLEMS:

Each shirt shall have a CSP emblem sewn on each sleeve by the vendor. Shoulder emblem shall NOT be creased. All emblems shall be furnished by CSP. An emblem is to be attached to each shirtsleeve; to be centered on the sleeve with the top center point centered on the shoulder strap and bottom point center on the sleeve crease. The top of the emblem will be set $\frac{3}{4}$ inch below the shoulder seam. Port of Entry shirts require a rocker above each shoulder emblem. On those, the top of the rocker will be set $\frac{3}{4}$ inch below the shoulder seam. The lower corners of the rockers will touch the top corners of the shoulder emblem. Backing material shall be trimmed to avoid fraying. Emblems are to be attached with the best quality vat dyed royal blue thread to match the emblem background.

Port of Entry Class B shirts will require a soft badge patch to be sewn on the left breast. It will be centered above the pocket flap with a $\frac{1}{2}$ inch gap between the top of the pocket flap and the bottom of the badge. A cloth name tag will be centered above and sewn directly above the right pocket flap. The name tag will be $\frac{7}{8}$ inches high made of black rolled fabric to conceal edges and have $\frac{3}{8}$ inch block lettering in gold or silver thread to match the color of the badge.

SIZING & MEASUREMENTS**SIZING – Male:**

<u>Sleeve Length:</u>	14.5	15	15.5	16	16.5	17	17.5	18	18.5	19.5
Short 32/33	x	x	x	x	x	x	x	x		
Medium 34/35	x	x	x	x	x	x	x	x	x	x
Long 36/37				x	x	x	x	x	x	x

Any sizes that fall outside those listed above will be considered special order.

SIZING - Female:

Finished garments will be furnished in Ladies sizes 32, 34, 36, 38, 40, 42, 44 and 46 standard sizes. Any sizes that fall outside those listed above will be considered special order.

The Rest of This Page Intentionally Left Blank